# GOODWE

# Lynx D Series

5.0kWh I High Voltage Battery

GoodWe's Lynx D Series is a high-voltage lithium battery specially designed for residential applications with superior performance. Compatible with GoodWe residential energy storage inverters, Lynx D Series comes with one-stopshop solutions saving you considerable time and effort. Each battery pack is designed as a standalone unit, incorporating a dedicated Battery Management System (BMS). This versatile system serves effectively in scenarios focused on self-consumption and backup power needs. With its sleek and modern design, it seamlessly blends into residential settings. The installation and commissioning have been made quicker and easier than ever with a userfriendly plug and play wiring system. Moreover, Lynx D batteries are engineered to support a mix of old and new battery packs, ensuring adaptable expansion and hasslefree replacement options.





#### **Smart Control**

- · Remote diagnosis and update via inverter
- · Auto reboot after undervoltage



### Superb Safety & Reliability

- · Reliable LFP technology with high cycle stability
- · IP66 protection for outdoor installation safety



#### Friendly & Thoughtful Design

- · Sleek and modern design
- · Plug and play wiring



## Flexible & Adaptable Applications

- · Modular design for parallel connection
- · Supports mixing new and old battery packs for flexible expansion



Technical Data		LX D5.0-10
Usable Energy (kWh) <sup>*1</sup>		5
Cell Type		LFP (LiFePO <sub>4</sub> )
Nominal Voltage (V)		Charge: 435; Discharge: 380
Output Voltage (V)		320 ~ 480
Nominal Power (kW)		3
Peak Power		5kW, 10s
Operating Temperature Range (°C)		Charge: 0 ~ +53; Discharge: -20 ~ +53
Relative Humidity		0 - 95%
Max. Operating Altitude (m)		4000
Communication		CAN
Weight (kg)		52
Dimensions (W × H × D mm)		700 × 380 × 170
Ingress Protection Rating		IP66
Mounting Method		Floor stacked / Wall-mounted
Standard and Certification	Safety	IEC62619, IEC60730, VDE2510-50, CE, CEC
	EMC	CE, RCM
	Transportation	UN38.3

<sup>\*1:</sup> Test conditions,100% DOD,0.2C charge & discharge at +25 ±3°C for battery system at beginning life. System Usable Energy may vary with different Inverter.
\*: Please visit GoodWe website for the latest certificates.
\*: All pictures shown are for reference only. Actual appearance may vary.